

## Swing Out Wall Mount

Innovatively designed to incorporate accessibility, convenience and security. Specifically designed for space-constrained applications mounts directly to building walls, freeing up valuable floor space. Wall Mount Enclosures deliver a cost-effective solution for your wiring and storage needs.

### FEATURES

- Designed and constructed to allow easy access to equipment from the front and back.
- 19" rack-mounting spacing
- Field reversible doors and body
- Key locks for security in both front and rear of enclosure
- Vented sides provides additional equipment cooling
- Textured powder coat finish - 7 standard colors

### WALL MOUNT INCLUDES

- Swing out locking body offers 14" useable depth, and 4" deep wall section for a total of 18" depth. Top and bottom cable access, (6) intake/exhaust vents, (2) fully adjustable mounting rails front to back
- Steel vented front door with swing handle lock
- Standard EIA-310-D specifications for mounting rail hole spacing (5/8", 5/8", 1/2")
- 20 Pack of 10-32 nut clips and screws

### OPTIONS

- Lexan® front door
- Cantilever shelves 19" wide
- Panel mount exhaust fan
- 19" rack-mountable power strip

### INSIDE USEABLE DIMENSIONS

Martin International Swing Out Wall Mount Enclosures are available in 2 size combinations (top dimensions)

- Height 24" or 42"
- Width 19"
- Depth 14" (Internal useable space of swing out body)

Custom Sizes, Configurations and Colors Upon Request

### ORDERING INFORMATION

Inside height, width and depth preceded with "WM" become the Swing Out Wall Mount Enclosure product number. **Example:** Unit pictured above is #WM241914

#WM\_\_\_\_\_

(hh/ww/dd)



**Martin International Enclosures Swing Out Wall Mount provides easy accessibility to equipment and cabling. The front door and body are hinged and field reversible.**